

Propeller	EMAX MT2205-2300KV				
	Thrust (g)	Volts (V)	Load (A)	Power (W)	Eff(g/W)
HQ6045	300	16.5	3.9	64.4	4.7
	400	16.3	4.9	79.9	5.0
	500	16.1	6.8	109.5	4.6
	1256	15.4	28.8	443.5	2.8

GF5045BN	300	16.4	3.9	64.0	4.7
	400	16.3	5.6	91.3	4.4
	500	16.2	7.6	123.1	4.1
	958	15.8	19.5	308.1	3.1

HQ5045BN	300	16.4	4.3	70.5	4.3
	400	16.3	6.3	102.7	3.9
	500	16.1	8.5	136.9	3.7
	1007	15.7	25.4	398.8	2.5

HQ5040x3	300	16.4	3.9	64.0	4.7
	400	16.2	5.8	94.0	4.3
	500	15.9	8.1	128.8	3.9
	982	15.5	21.5	333.3	2.9

GF5045x3	300	16.4	4.1	67.2	4.5
	400	16.2	6.2	100.4	4.0
	500	15.9	8.7	138.3	3.6
	942	15.5	21.7	336.4	2.8

HQ4040x3	300	16.5	5.4	89.1	3.4
	400	16.3	7.4	120.6	3.3
	500	16.1	10.2	164.2	3.0
	680	16.0	15.6	249.6	2.7

GF4045BN	300	16.3	5.3	86.4	3.5
	400	16.1	8.1	130.4	3.1
	500	16.0	10.7	171.2	2.9
	652	16.0	16.1	257.6	2.5

Cobra 2205-2300KV				
Thrust (g)	Volts (V)	Load (A)	Power (W)	Eff(g/W)
300	16.5	3.9	64.4	4.7
400	16.3	6.4	104.3	3.8
500	16.1	8.5	136.9	3.7
1005	15.6	28.2	439.9	2.3

300	16.4	4.1	67.2	4.5
400	16.3	6.1	99.4	4.0
500	16.1	8.6	138.5	3.6
847	15.7	20.5	321.9	2.6

300	16.3	5.0	81.5	3.7
400	16.0	8.2	131.2	3.0
500	15.6	10.6	165.4	3.0
820	15.3	24.3	371.8	2.2

300	16.4	4.3	70.5	4.3
400	16.2	6.6	106.9	3.7
500	15.8	9.5	150.1	3.3
854	15.5	22.6	350.3	2.4

NO DATA				
---------	--	--	--	--

300	16.2	5.6	90.7	3.3
400	15.9	8.2	130.4	3.1
500	15.5	11.9	184.5	2.7
634	15.7	16.4	257.5	2.5

300	16.4	6.0	98.4	3.0
400	16.1	9.4	151.3	2.6
500	15.8	13.0	205.4	2.4
636	16.0	17.2	275.2	2.3

RCX H2205-2350KV				
Thrust (g)	Volts (V)	Load (A)	Power (W)	Eff(g/W)
300	16.6	3.4	56.4	5.3
400	16.5	5.3	87.5	4.6
500	16.4	7.4	121.4	4.1
1038	16.2	24.9	403.4	2.6

300	16.5	3.6	59.4	5.1
400	16.5	5.5	90.8	4.4
500	16.4	7.9	129.6	3.9
862	16.2	17.7	286.7	3.0

NO DATA				
---------	--	--	--	--

300	16.4	3.8	62.3	4.8
400	16.2	5.9	95.6	4.2
500	16.1	8.2	132.0	3.8
842	15.6	19.2	299.5	2.8

300	16.5	4.3	71.0	4.2
400	16.3	6.5	106.0	3.8
500	16.1	9.0	144.9	3.5
832	15.9	21.0	333.9	2.5

300	16.5	5.2	85.8	3.5
400	16.3	7.3	119.0	3.4
500	16.0	10.2	163.2	3.1
644	16.2	14.1	228.4	2.8

300	16.2	5.2	84.2	3.6
400	16.0	8.5	136.0	2.9
500	15.7	11.1	174.3	2.9
608	15.9	14.5	230.6	2.6